

KWC DOMO









KWC-No. **Finish**

10.061.002.127 splendure™ stainless steel

7 3/32" spout length

10.061.002.000

7 3/32" spout length

10.061.003.127

9 1/4" spout length

10.061.003.000

chrome

splendure™ stainless steel

chrome

9 1/4" spout length

Kitchen

Pull-Out Faucet with flexguard™ & jetclean™

Single-lever mixer

• lever installation right side only

Child safety: cold water flow in lever position towards the front Detachable for installation below windows - detached 5 1/8" flexguard™ - Sealing membrane between lever and cap:

- protects the inside of the faucet
- to prevent liquid penetrating from outside

Space between wall and mounting hole minimum of 1" Pull-out spray with KWC jetclean TM

- pull-out length up to 27 1/16"
- lockable regular spray
- automatic diverter reset
- hose surface to fit faucet surface
- hose guide secures hose back in place
- swivel range 360°

KWC L 39 control cartridge

- ceramic discs
- variable flow rate and temperature
- temperature and flow rate limitation

Flexible connection hoses 3/8 " compression M33 x 1.5 threaded sleeve fastening Mounting hole size ø1 3/8"

Flow rate max 1.75 gpm (60 psi) Flow rate needle spray max 1.75 gpm (60 psi)

Catalog page 72