



KWC-No.	Finish
10.201.122.127 8 7/16" spout length	splendure™ stainless steel
10.201.122.000 8 7/16" spout length	chrome

Kitchen
Pull-Down Faucet with luminaqua®
LED-Technology

- Single-lever mixer
 - lever installation right side only
- Child safety: cold water flow in lever position towards the front
- Space between wall and mounting hole minimum of 1 5/8" C/C
- Covered pull-out spray
 - ergonomic shape and spout alignment for ease of handling
 - KWC jetclean™ technology
 - Cascade® limescale protection aerator
 - Caché® adjustable aerator
 - automatic diverter reset
 - integrated ON/OFF push-button with automatic shut-off after 30 minutes
 - pull-out length up to 19 1/16"
 - hose surface to fit faucet surface
 - hose guide secures hose back in place
 - swivel range 270°
- KWC S 25 control cartridge
 - ceramic discs
 - variable flow rate and temperature
- Flexible connection hoses 3/8" compression
- M33 x 1.5 threaded sleeve fastening
- Mounting hole size ø1 3/8"
- Includes:
 - plug power supply 100-240 V / operating voltage 6.75 V / cable length 43 5/16"

Flow rate max 1.75 gpm (60 psi)
 Flow rate needle spray max 1.75 gpm (60 psi)